

### Red Pre-Insulated Terminals

#### LIP BLADE - LB RANGE

- 0.5-1.6mm<sup>2</sup> conductor
- 415V
- Supplied in re-sealable bags



Part No.	Description	UOM	Pack Qty
LBR-3	Lip Blade width 3mm Red	EA	50
LBR-3DG	Lip Blade width 3mm Red DG	EA	50
LBR-5DG	Lip Blade width 5mm Red DG	EA	50

#### FLAT BLADE - FB RANGE

- 0.5-1.6mm<sup>2</sup> conductor
- 415V
- Supplied in re-sealable bags



Part No.	Description	UOM	Pack Qty
FBR-2	Flat Blade width 2.0mm Red	EA	100
FBR-2DG	Flat Blade width 2.0mm Red DG	EA	100
FBR-2.3/17	Flat Blade width 2.0mm Red 17mm long	EA	100
FBR-3	Flat Blade width 3.0mm Red	EA	100
FBR-3DG	Flat Blade width 3.0mm Red DG	EA	100

#### BULLET CONNECTOR - BC RANGE

- 0.5-1.6mm<sup>2</sup> conductor
- 415V
- Supplied in re-sealable bags



Part No.	Description	UOM	Pack Qty
BCMRDG	Bullet Connector Male Red 4mm DG	EA	100
BCFRDG	Bullet Connector Female Red 4mm DG	EA	25

#### IN LINE SPLICE - ILS RANGE

- 0.5-1.6mm<sup>2</sup> conductor
- 415V
- Supplied in re-sealable bags



Part No.	Description	UOM	Pack Qty
ILSR	In Line Splice Red	EA	50
ILSRDG	In Line Splice Red DG	EA	50

#### QUICK CONNECTOR RANGE - QC RANGE

- 0.5-1.6mm<sup>2</sup> conductor
- 415V
- Supplied in re-sealable bags



Part No.	Description	UOM	Pack Qty
QCPBR-6.4DG	Quick Connector Piggy Back Red 6.4*0.8	EA	50
QCR-6.4DG	Quick Connector Red 6.4* 0.8mm Tab DG	EA	100
QCRFI-6.4DG	Quick Connector Fully Ins.6.4*0.8 Red	EA	50
QCMTR-6.4DG	Quick Connector Male Tab 6.4*0.8mm Red	EA	100
ECR	Wire Spl.Comb.XSect.1-2.3mm	EA	50